

# Polycom VVX 600 Business Media Phones

## SIMPLICITY AND EASE OF USE

The intuitive gesture-based, multi-touch user interface of the Polycom VVX 600 phone makes navigation easy and requires minimal training. Combines ergonomic design, Polycom® HD Voice™ quality and a large, high resolution color, multi-touch screen.

## MAXIMIZE PRODUCTIVITY

The Polycom VVX 600 improves personal productivity by complementing the workplace applications on their computer. Users can view and manage their Microsoft Exchange Calendars, receive meeting reminders and alerts, access the corporate directory and Instant Messaging/presence status right on their phone display. They can also extend their PC's desktop to include the Polycom VVX 600 phone's screen for mouse/keyboard navigation and interaction.

## BEST-IN-CLASS DEPLOYMENT AND ADMINISTRATION

The Polycom VVX 600 phone is easy to deploy and simple to manage through the Web-based, intuitive configuration tool. Its enterprise-grade Zero Touch Provisioning and server based configuration on large scale deployments as well as our redirection services, gives your administrators the ability to easily provision and maintain a large number of phones throughout the entire enterprise. The built-in, broad interoperability capabilities allow IT departments to leverage previous IT infrastructure investments and achieve easy integration with third-party UC and productivity applications.

## HIGHLY CUSTOMIZABLE AND EXPANDABLE

The Polycom VVX 600 phone provides personalized information at a glance, through built-in web applications and a digital photo frame. Polycom VVX 600 users access streaming content using the included video playback feature. The Polycom VVX 600 phone comes ready for future expansion modules and applications such as video conferencing with the Polycom VVX Camera.



A premium business media phone delivering best-in-class desktop productivity for busy corporate executives and managers.

The Polycom® VVX® 600 phone is a premium business media phone designed to enhance collaboration and personal productivity.



## Polycom VVX 600 Specifications

### USER INTERFACE FEATURES

- Gesture based, multi-touch capable capacitive touchscreen
- 4.3in LCD (480x272 pixel) resolution
- 16:9 aspect ratio
- Screen saver and digital picture frame mode
- On-screen virtual keyboard
- Voicemail and videomail support<sup>2</sup>
- Dual USB ports (2.0 compliant) for media and storage applications
- Integrated Bluetooth 2.1 EDR
- Adjustable base height
- Unicode UTF-8 character support. Multilingual user interface including Chinese, Danish, Dutch, English (Canada/ US/UK), French, German, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Slovenian, Spanish, and Swedish

### AUDIO FEATURES

- Polycom HD Voice™ 1
- Polycom Acoustic Clarity™ technology providing full-duplex conversations, acoustic echo cancellation and background noise suppression—Type 1 compliant (IEEE 1329 full duplex)
- Frequency response: 14 KHz for handset, optional headset and hands-free speakerphone modes
- Codecs: G.711 (A-law and  $\mu$ -law), G.729AB, G.722, G.722.1, G.722.1C, iLBC
- Individual volume settings with visual feedback for each audio path
- Voice activity detection
- Comfort noise generation
- DTMF tone generation (RFC 2833 and in-band)
- Low-delay audio packet transmission

- Adaptive jitter buffers
- Packet loss concealment

### HEADSET AND HANDSET COMPATIBILITY

- Bluetooth headset pairing (HFP/HSP)
- Dedicated RJ-9 headset port
- Hearing aid compatibility to ITU-T P.370 and TIA 504A standards
- Compliant with ADA Section 508 Subpart B 1194.23 (all)
- Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids
- Compatible with commercially-available TTY adapter equipment
- USB headsets are supported. (See Support list of compatible headsets.)

### CALL HANDLING FEATURES<sup>2</sup>

- 16 lines (registrations)
- Shared call/bridged line appearance
- Busy Lamp Field (BLF)
- Flexible line appearance (one or more line keys can be assigned for each line extension)
- Distinctive incoming call treatment/ call waiting
- Call timer and call waiting
- Call transfer, hold, divert (forward), pickup
- Called, calling, connected party information
- Local three-way audio conferencing
- One-touch speed dial, redial
- Remote missed call notification
- Do not disturb function
- Electronic hook switch capable
- Local configurable digit map/dial plan

## Benefits

- Improve productivity for executives and managers through larger, color multi-touch display and more line appearances
- Make more efficient and productive calls with the unparalleled voice clarity of Polycom® HD Voice™
- Turn your Polycom VVX® Business Media Phone into a video conference ready desktop video conferencing solution with an optional Polycom VVX Camera
- Improve work space mobility through Bluetooth headset integration
- The Polycom Zero Touch Provisioning and web based configuration tool makes the Polycom VVX 600 simple to deploy, upgrade, and maintain
- Leverage previous IT infrastructure investments – deploy Polycom VVX 600 business media phones on your existing network without needing to upgrade your call control platform
- Easily integrate with third-party with UC and productivity applications for broad, standards- based, open APIs

## OPEN APPLICATION PLATFORM

- WebKit enabled full browser that supports HTML5, CSS, SSL security, and JavaScript
- Supports Polycom Apps SDK and API for third-party business and personal applications
- Bundled with Polycom UC Software:
- Corporate Directory Access using LDAP
- Local Voice Call Recording on USB flash drive
- Visual Conference Management

## NETWORK AND PROVISIONING

- SIP Protocol Support
- SDP
- IETF SIP (RFC 3261 and companion RFCs)
- Two-port Gigabit Ethernet switch
  - › 10/100/1000Base-TX across LAN and PC ports
  - › Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment
- Conforms to IEEE802.3-2002 (Clause 28) for link Partner auto-negotiation
- Manual or dynamic host configuration protocol (DHCP) network setup
- Time and date synchronization using SNTP
- FTP/TFTP/HTTP/HTTPS server-based central provisioning for mass deployments
- Support for Polycom Zero Touch Provisioning (ZTP)
- Provisioning and call server redundancy supported<sup>2</sup>
- QoS Support—IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DSCP
- VLAN – CDP, DHCP VLAN discovery, LLDP-MED for VLAN discovery
  - › Network Address Translation (NAT) – support for static configuration and “Keep-Alive” SIP signaling
- RTCP and RTP support
- Event logging
- Syslog
- Hardware diagnostics

- Status and statistics reporting
- IPv4
- TCP
- UDP
- DNS-SRV

## SECURITY

- 802.1X Authentication and EAPOL
- Media encryption via SRTP
- Transport Layer Security (TLS)
- Encrypted configuration files
- Digest authentication
- Password login
- Support for URL syntax with password for boot server address
- HTTPS secure provisioning
- Support for signed software executables

## POWER

- Built-in auto sensing IEEE 802.3at
- Power over Ethernet (Class 4). Backwards compatibility with IEEE 802.3af

## APPROVALS

- Argentina CNC
- South Africa ICASA
- Saudi Arabia CITC
- India TEC
- Japan MIC/VCCI Class B
- Malaysia SIRIM
- Israel MOC
- Singapore IDA
- Taiwan NCC<sup>3</sup>
- Mexico NOM-121
- FCC Part 15 (CFR 47) Class B
- ICES-003 Class B
- EN55022 Class B
- CISPR22 Class B
- VCCI Class B
- EN55024
- EN61000-3-2; EN61000-3-3
- NZ Telepermit
- Korea KC
- UAE TRA
- Russia GOST-R
- Brazil ANATEL<sup>3</sup>
- Australia A&C Tick

- ROHS compliant
- China CCC<sup>3</sup>
- Safety
- UL 60950-1
- CE Mark
- CAN/CSA-C22.2 No. 60950-1-03
- EN 60950-1
- IEC 60950-1
- AS/NZS 60950-1

## OPERATING CONDITIONS

- Temperature: 0 to 40°C (+32 to 104°F)
- Relative Humidity: 5% to 95%, noncondensing
- Storage Temperature: -40 to +70° C (-40 to +160° F)

## POLYCOM VVX 600 COMES WITH:

- Polycom VVX 600 console
- Handset with handset cord
- Network (LAN) Cable – CAT-5E
- Quick Start Guide
- External Universal AC Adaptor (optional, 48V 380mA DC)

## SIZE (W X H X D)

- 8.5 x 6 x 7 in (21 x 15 x 18 cm)

## PART NUMBERS

- 2200-44,600 -02s — WW PoE

## WEIGHT

- Unit weight: 2.0 lbs (0.9 kg)
- Unit box dimensions/weight
- 11.4 x 7.9 x 3.5 in (2 c x 20 x 2 cm)
- 3.1 lbs (1.4 kg)

## MASTER CARTON QUANTITY

- Five ( )

## COUNTRY OF ORIGIN

- China

## WARRANTY

- One year

<sup>1</sup>To enjoy all the benefits of Polycom® HD Voice™ when using the phone in the headset mode, you must use a wideband headset.

<sup>2</sup>Most software-enabled features and capabilities must be supported by the server. Please contact your IP PBX/Softswitch vendor or service provider for a list of supported features.

<sup>3</sup>Planned future compliance